

# master view™ max USB & PS/2 KVM Switch

Multiplatform Support!



(Front View)



(Rear View)



Diagram



Model: **CS-1754**  
**CS-1758**

## Features

- One console controls 4/8 computers
- USB console, pure USB KVM switching
- Dual interface supports PS/2 and USB connections to the computers\*
- OSD-On Screen Display
- Multiplatform support: PC, Mac, Sun and Linux systems
- Cascades to 3 levels - capable of supporting up to 64/512 PCs
- Hotkey, OSD selection for OS
- Supports Windows 98SE or higher, Mac OS 8.6 or higher, Linux Red Hat 7.1 or higher, and Sun host systems
- Audio enabled
- Firmware Upgradable

\* Specify PS/2 or USB interface for each cable upon purchase

## Specifications:

Function		CS-1754	CS-1758	
PC connections	Direct	4	8	
	Max via Cascade	64	512	
Connectors	Console	K/B	1 x USB Type-A (F)	1 x USB Type-A (F)
		Video	1 x HDB15 (F)	1 x HDB15 (F)
		Mouse	1 x USB Type-A (F)	1 x USB Type-A (F)
		Speaker	1 x Earphone Jack (F)	1 x Earphone Jack (F)
		Microphone	1 x Earphone Jack (F)	1 x Earphone Jack (F)
	PC Connectors	K/B	4 x SPHD15 (F)	8 x SPHD15 (F)
		Video		
		Mouse		
		Speaker		
		Microphone		
Firmware upgrade	1 x RJ 11 (F)	1 x RJ 11 (F)		
Power Jack	1	1		
LEDs	On Line / Selected	4 Orange / 4 Green	8 Orange / 8 Green	
Port Selection	Push button, Hotkey, OSD	Push button, Hotkey, OSD	Push button, Hotkey, OSD	
VGA Resolution		2048 x 1536	2048 x 1536	
Scan Interval		5 seconds (fixed)	5 seconds (fixed)	
Housing		Metal	Metal	
Weight		2640g	2720g	
Dimensions (L x W x H)		432 x 154 x 45mm	483 x 154 x 45mm	