

Commodity : STICKY MAT

SPECIFICATION

Test item		Unit	Standard spec
Dimension	Thickness	40 um/layer	1.2mm
	Width ×Length	inch	18"x36"/24"x36"/26"x45"
Function		—	Normal sticky mat
Color		—	blue
Layer		sheets	30 sheets
Raw material	Film	—	LDPE
	Adhesive	—	Acrylic
Adhesive strength		g/25mm	200-700
Peeling strength		g/25mm	400+/-100
Adhesion of double side adhesive film		g/25mm	700+/-100
Tensile strength		kgf/cm ²	120 ↑
Elongation		%	250 ↑
Heat resistance		—	70 ± 3 °C/48Hr
Cold resistance		—	-13 ± 3 °C/48Hr
Weatherability		—	200Hr

SPECIFICATION

Test item		Unit	Standard spec
Dimension	Thickness	45 um	50+45*30+50=1450um
	Width ×Length	mm	600x900
		inch	24"×36"
Function		—	Normal sticky mat
Color		—	blue
Layer		sheets	30 sheets
Raw material	Film	—	LDPE
	Adhesive	—	Acrylic
Adhesive strength		g/25mm	200-700
Peeling strength		g/25mm	400+/-100
Adhesion of double side adhesive film		g/25mm	700+/-100
Tensile strength		kgf/cm ²	120 ↑
Elongation		%	250 ↑
Heat resistance		—	70 ± 3 °C/48Hr
Cold resistance		—	-13 ± 3 °C/48Hr
Weatherability		—	200Hr

DIREKTRONIK

Direktronik AB tel. 08-52 400 700 www.direktronik.se