



5SC1500i

Eaton 5SC 1500 VA Tower

General

Topology	Line-interactive high frequency with booster + fader, pure sinewave output
Configuration	Tower
Part Number	5SC1500i
Color	Black
Rating (VA/Watts)	1500/1050
Dimensions (H x W x D, mm)	210 x 150 x 410
Weight (kg)	15.2
Warranty	2 years

Electrical Input

(1) IEC-320-C14

Connection



Input Voltage Range	184V-276V
Nominal Voltage	230V
Input frequency Range Without Using Batteries	45–55Hz (50Hz system), 55–65Hz (60Hz system)

Electrical Output

Voltages

230V (+6/-10 %) (Adjustable to 220V/230V/240V)

Outlets

(8) IEC-320-C13



Output Frequency

50/60Hz +/-0.1 % (autosensing)

Battery

Battery Management

ABM®, Automatic battery test, deep discharge protection

Communications

Communication Ports

1 USB port + 1 RS232 serial port (USB and RS232 ports cannot be used simultaneously)

Environmental & Standards

Audible Noise

<40 dB

Operating Temperature

0-35°C

Safety markings

IEC/EN 62040-1, UL 1778

EMC Markings

IEC/EN 62040-2

Approvals

CE, CB report (TUV)

In the interests of continuous product improvement, all specifications are subject to change without notice.