



Specifications

Fiber Mode				SM
Type	LC/APC-LC/APC			
Diameter(mm)	φ 2.0mm 9/125 SMLSZH (yellow)			
Insertion Loss(dB)	APC	≤0.3	APC	≤0.3
Return Loss(dB)		≥60		≥60
Housing Color	PLUG1	Green	PLUG2	Green
Boot Color	BOOT1	White	BOOT2	White
Operating Temperature(°C)	-20~+75			
Storage Temperature(°C)	-20~+85			
Operating Wavelength(nm)				1310

NOTE:

All FIBER CABLE ARE TESTED BY INSERTION LOSS/RETURN LOSS TEST STATION AND INTEGRATED OPTICALFIBER END FACE INSPECTION EXPERTS

⑤	BOOT	1PCS	WHITE
④	PLUG	1PCS	LC/APC GREEN
③	BOOT	1PCS	WHITE
②	PLUG	1PCS	LC /APC GREEN
①	CABLE	1PCS	OD:2.0mm 9/125 SM OS2 LSZH (YELLOW)
NO.	PARTS NAME	Q'TY	SPECIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	LCLC-3S-APC
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:
PATCH CORD LC/APC -LC/APC DX
9/125 SM OS2 LSZH OD:2mm

