

Overview

Jackets

HP ElitePad Security Jacket Cover	E6N31AA
HP ElitePad Security Jacket with Smart Card Reader	E5S90AA
HP ElitePad Security Jacket HP ElitePad Security Jacket with Smart Card Reader and Fingerprint Reader	E5S91AA
HP ElitePad Security Jacket HP ElitePad Security Jacket with Smart Card Reader and Fingerprint Reader	H7A97AA
HP ElitePad Expansion Jacket	H4J85AA
HP ElitePad Expansion Jacket with Battery	D2A23AA
HP ElitePad Productivity Jacket	D6S54AA

Power

HP ElitePad Expansion Jacket Battery	H4F20AA
HP ElitePad 10W AC Adapter	H4K08AA
HP 40W Smart AC Adapter	H5W93AA
HP Multi-Tablet Charging Module (separate specs)	H4W98AA
HP ElitePad Power/Ethernet Adapter New!	F9D31AA

Docking Station

HP ElitePad Dockable Case	F1M97AA
HP ElitePad Docking Station	COM84AA

Adapters

HP ElitePad USB 3.0 Adapter New!	E8F98AA
HP ElitePad 12W USB Auto Adapter (w/cable) New!	F5V87AA
HP ElitePad USB Adapter	H3N46AA
HP ElitePad Smart AC Adapter	H3N47AA
HP ElitePad HDMI & VGA Adapter	H3N45AA
HP ElitePad Serial Adapter	H3N50AA
HP ElitePad Ethernet Adapter	H3N49AA
HP ElitePad SD Card Reader	H3N48AA

Input/Output

HP Slim Bluetooth Keyboard	H4Q44AA
HP Executive Tablet Pen G2 New!	F3G73AA

Cases

ElitePad Leather Slip Case	E5L02AA
HP ElitePad Case	H4R88AA
HP ElitePad Rugged Case	H4R89AA
HP ElitePad Rugged Case G2 New!	F5A38AA

Technical Specifications

Jackets

HP ElitePad Security Jacket Cover

Dimensions (H x W x D)	10.34 x 7.83 x 0.80 in (262.7 x 177.8 x 2.1 mm)
Materials	
Exterior cover material	Microfiber short hair
Exterior cover surface	Smooth
Exterior cover color	Grey
Interior color	Grey
Cover strip material	Graphite Polycarbonate
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

HP ElitePad Security Jacket with Smart Card Reader

Dimensions (H x W x D)	10.57 x 7.75 x 0.65 in (268.4x 196.9 x 16.5 mm)	
Weight	0.70 lb (317 g) Jacket only	
USB ports	(1) USB 3.0	
Audio connectors	Combo stereo/headphone jack	
Other connectors	(1) HDMI	
Stand-alone power requirements	Normal Operating Voltage	6.5 V
	Average Operating Power	8.5 W
	Max Operating Power	< 40 W
Temperature	Operating	32° to 95° F (0° to 35° C)
	Non-operating	4° to 140° F (-20° to 60° C)
Relative humidity	Operating	10% to 90%, relative humidity
	Non-operating	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
Altitude	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Shock	Operating	40 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random vibration	Operating	10-500 Hz, 0.5 grms
	Non-operating	10-500 Hz, 1.0 grms
Option kit contents	HP ElitePad Security Jacket with Smart Card Reader, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

NOTE: Weight is measure using a PV unit and aluminum CAC cover, cover/kick stand is not included.

Technical Specifications

HP ElitePad Security Jacket HP ElitePad Security Jacket with Smart Card Reader and Fingerprint Reader

Dimensions (H x W x D)	10.57 x 7.75 x 0.65 in (268.4x 196.9 x 16.5 mm)	
Weight	0.70 lb (317 g) Jacket only	
USB ports	(1) USB 3.0	
Audio connectors	Combo stereo/headphone jack	
Other connectors	(1) HDMI	
Stand-alone power requirements	Normal Operating Voltage	6.5 V
	Average Operating Power	8.5 W
	Max Operating Power	< 40 W
Temperature	Operating	32° to 95° F (0° to 35° C)
	Non-operating	4° to 140° F (-20° to 60° C)
Relative humidity	Operating	10% to 90%, relative humidity
	Non-operating	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
Altitude	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Shock	Operating	40 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random vibration	Operating	10-500 Hz, 0.5 grms
	Non-operating	10-500 Hz, 1.0 grms
Option kit contents	HP ElitePad Security Jacket with Smart Card Reader, documentation	
Compatibility	NOTE: Weight is measure using a PV unit and aluminum CAC cover, cover/stand is not included. HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad Expansion Jacket Cover

Dimensions (H x W x D)	10.77 x 8.30 x 0.89 in (273.65x 210.75x 22.60mm)
Shell material	Black rubber PU
Protective shell material	Black TPU
Lining material	Black Microflex lining
Hardware	Black plastic
Option kit contents	HP ElitePad Protective Jacket Cover and documentation
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

Technical Specifications

HP ElitePad Expansion Jacket

Dimensions (H x W x D)	10.60 x 8.05 x 0.69 in (269.2x 204.6 x 17.5 mm)	
Weight	0.56 lb (254 g) (jacket only)	
USB ports	(2) USB 2.0 ports	
Audio connectors	Combo stereo/headphone jack	
Other connectors	(1) HDMI, (1) HCSD	
Stand-alone power requirements	Normal Operating Voltage	6.5 V
	Average Operating Power	8.5 W
	Max Operating Power	< 40 W
Temperature	Operating	32° to 95° F (0° to 35° C)
	Non-operating	4° to 140° F (-20° to 60° C)
Relative humidity	Operating	10% to 90%, relative humidity
	Non-operating	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
Altitude	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Shock	Operating	40 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
Random vibration	Operating	10-500 Hz, 0.5 grms
	Non-operating	10-500 Hz, 1.0 grms
Option kit contents	HP ElitePad Expansion Jacket, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad Expansion Jacket With Battery

Dimensions	Battery and Jacket (H x W x D)	10.60 x 8.05 x 0.69 in (269.2x 204.6 x 17.5 mm)	
	Battery only (H x W x D)	4.3 x 118.5 x 200 mm	
Weight	Jacket and Battery only	0.86 lbs (450 g)	
	Jacket only	0.57 lbs (260 g)	
	Battery only	0.42 lbs (190 g)	
Specs		HP ElitePad Main Battery	HP ElitePad Jacket Battery
Battery Cells/Type		Lithium-ion Polymer	Lithium-ion Polymer
Energy	Voltage	7.4V	7.4V
	Amp-hour capacity	3.38Ah	2.96Ah
	Watt-hour capacity	25Wh	21Wh
Temperature Battery	Operating (Charging)	32° to 113° F (0° to 45° C)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 140° F (-10° to 60° C)	14° to 140° F (-10° to 60° C)
	Non-operating	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)
Temperature Jacket Only		32° to 95° F (0° to 35° C)	4° to 140° F (-20° to 60° C)

Technical Specifications

Battery Re-Charge Time	System in OFF or Standby Mode	2.5~3.5 hours	1.5 to 3 hours
	System ON	2.5 to 5 hours	1.5 to 4 hours
Relative humidity (Jacket)	10% to 90%, relative humidity 5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature		
Altitude (Jacket)	-50 to 10,000 ft (-15.24 to 3,048 m) -50 to 40,000 ft (-15.24 to 12,192 m)		
Shock (Jacket)	40 G, 2 ms, half-sine 200 G, 2 ms, half-sine		
Random vibration (Jacket)	10-500 Hz, 0.5 grms 10-500 Hz, 1.0 grms		
Fuel Gauge LED on Battery	NO		
Warranty	1 year		
Ports on Jacket	(2) USB 2.0 ports, combo stereo/headphone, (1) HDMI, (1) HCSD		
Stand-alone power requirements for Jacket	6.5 V 8.5 W < 40 W		
Option kit contents	HP ElitePad Expansion Jacket, battery, documentation		
Power conservation	Standby, hibernation		
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet		

HP ElitePad Productivity Jacket

Dimensions (H x W x D)	10.60 x 8.50 x 0.91 in (269.2x 215.9 x 23 mm)		
Weight	<1.87 lb (< 850 g)		
Stand-alone power requirements	Average Operating Power	1.0 W	
	Max Operating Power	< 10 W	
Ports	(2) USB 2.0 ports Power connector		
Other connectors	(1) HD card slot		
Audio connectors	Combo stereo/ headphone and microphone jack		
Additional features	Integrated wired keyboard Digital pen holder 3 adjusting viewing positions		
Option kit contents	HP ElitePad Productivity Jacket, documentation		
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet		

Power

Technical Specifications

HP ElitePad Expansion Jacket Battery

Dimensions (H x W x L)	0.17 x 4.67 x 7.88 in (4.3 x 118.6 x 200 mm)	
Weight	0.41 lb (186 g)	
Cell Type	Lithium-ion Polymer	
Energy	Voltage	7.4V
	Amp-hour capacity	2.96Ah
	Watt-hour capacity	21Wh
Temperature	Operating (charging)	32° to 113° F (0° to 45° C)
	Operating (discharging)	14° to 140° F (-10° to 60° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
Battery Recharge Time	System in OFF or Standby Mode	1.5 to 3 hours
	System ON	1.5 to 4 hours
Fuel Gauge LED	No	
Warranty	1 year	
Optional Travel Battery Available	No	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad 10W AC Adapter

Dimensions (H x W x D)	2.56 x 2.16 x 1.14 in (65 x 55 x 29 mm)	
Weight	4.06 oz (115 g)	
Input	90 to 265 VAC	
Input Efficiency	76.6% min at 115 VAC	
Input frequency range	47 to 63 Hz	
Input AC current	1.0 A at 90 VAC	
Output	Output power	10W
	DC output	9.00V
	Hold-up time	5 msec at 115 VAC input
	Output current limit	<3.5A, Over voltage protection- 20V max automatic shutdown
Connector	Tyco 70pin connector	
Environmental Design	Operating temperature	41° to 95° F (5° to 35° C)
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
	Altitude	0 to 10,000 ft (0 to 3,048 m)
	Non-Operating altitude	0 to 50,000 ft (0 to 15,240 m)
	Humidity	Up to 95%
	Storage Humidity	Up to 95%

Technical Specifications

EMI and Safety Certifications	Worldwide safety and EMC approvals including CE, UL, cUL, GS, Australian Electric Permit, RCM, NOM, CCC, KC, CU, S mark, BSMI, ISC, PSE, PSB, NRcan, Ukrain and SII
Option kit contents	HP ElitePad 10W AC Adapter, adapter duckhead(s), documentation
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

HP 40W Smart AC Adapter

Dimensions (H x W x D)	3.67 x 1.57 x 1.18 in (93 x 40 x 30 mm)
Weight	8.64 oz (245 g)
Input	90 to 265 VAC
Input Efficiency	84% min at 115 VAC
Input frequency range	47 to 63 Hz
Input AC current	1.0 A at 90 VAC
Output	
Output power	40W
DC output	9.50V
Hold-up time	5 msec at 115 VAC input
Output current limit	5A
Connector	HP Smart Barrel
Environmental Design	
Operating temperature	41° to 95° F (5° to 35° C)
Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
Altitude	0 to 10,000 ft (0 to 3,048 m)
Non-Operating altitude	0 to 50,000 ft (0 to 15,240 m)
Humidity	Up to 95%
Storage Humidity	Up to 95%
EMI and Safety Certifications	Worldwide safety and EMC approvals including CE, UL, cUL, GS, Australian Electric Permit, RCM, NOM, CCC, KC, CU, S mark, BSMI, ISC, PSE, PSB, NRcan, Ukrain and SII
Option kit contents	HP 40W Smart AC Adapter, power cord, documentation
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

Technical Specifications

HP ElitePad Power/Ethernet Adapter

Dimensions (H x W x L)	0.602 x 2.165 x 215.56 in (15.3 x 55 x 547.54 mm)	
Weight	1.69 lb (48 g)	
RMN No.	HSTNN-GD11	
Device interface	RJ45 Ethernet 70-pin female connector	
Connectors	Device output: RJ45 Ethernet , 70-pin female connector Host input: 70pin male Connector	
Supported	10/100 Mbps / Elitepad power adapter	
Operating Temperature	0-40°C (32-104°F)	
Storage Temperature	-10~70°C (14~158°F)	
System Requirements	Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft Windows XP Home or Professional with Service Pack 3, Windows 8.	
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	
Box contents	HP Power/RJ45 Adapter Cable, AU / WW Warranty Card, Quick Installation Guide	

Docking

HP ElitePad Dockable Case

Dimensions (H x W x D)	10.43 x 7.09 x 0.39 in (264 x 180 x 9.91 mm)
Weight	.44 lb (200 g)
Materials	Plastic cradle Microfiber cover Magnets inside flap Stand function
Option kit contents	HP ElitePad Dockable Case and documentation
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

Technical Specifications

HP ElitePad Docking Station

Dimensions (H x W x D)	4.83 x 5.34 x 2.24 in (122.8 x 135.7 x 57 mm)	
Weight	1.48 lb (670 g)	
USB ports	(3) USB 2.0 ports, (1) Power-USB 2.0 port	
Audio connectors	Combo stereo/headphone jack	
Other connectors	(1) HDMI, (1) VGA, (1) RJ-45, (1) Smart AC adapter, (1) charge LED	
Stand-alone power requirements	Normal Operating Voltage	19.5 V
	Average Operating Power	8.5 W
	Max Operating Power	< 40 W
Temperature	Operating	32° to 95° F (0° to 35° C)
	Non-operating	4° to 140° F (-20° to 60° C)
Relative humidity	Operating	10% to 90%, relative humidity
	Non-operating	5% to 90% relative humidity, 101.6° F (38.7° C) maximum wet bulb temperature
Altitude	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Shock	Operating	N/A
	Non-operating	200 G, 2 ms, half-sine
Random vibration	Operating	N/A
	Non-operating	10-500 Hz, 1.0 grms
Option kit contents	HP ElitePad Docking Station, 40W Smart AC adapter, power cord, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

Adapters

HP ElitePad USB 3.0 Adapter

Host Interface	70 pin	
Device interface	USB 3.0	
Connectors	Signal output:	USB female Connector
	Host input:	70PIN male Connector
Supported	Bus Power 5V output	
Operating Temperature	0-40°C (32-104°F)	
Storage Temperature	-10~70°C (14~158°F)	
System Requirements	Software	Microsoft Windows 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft® WindowsXP Home or Professional with Service Pack 3, Windows 8.
	Mechanical	Dimensions (H x W x L)
	Weight	Unpackaged: 0.60 oz (17 g)
Environmental		

Technical Specifications

Operating	Temperature	(0° to 55° C)
	Humidity:	10% to 90%, relative humidity
	Altitude: Operating	100, 00 feet and Non-Operating 30,000 feet used in vehicles.
Box contents	HP ElitePad USB 3.0 Adapter, AU / WW Warranty Card, Quick Installation Guide	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad 12W USB Auto Adapter (w/cable)

Host Interface	HP ElitePad docking connector	
Device interface	USB3.0	
Connectors	Signal output: USB female connector	
	Host input: 70-pin male connector	
Supported		
Operating Temperature	0-40°C (32-104°F)	
Storage Temperature	-10~70°C (14~158°F)	
System Requirements	Software	Microsoft® Windows® 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft® Windows® XP Home or Professional with Service Pack 3, Windows 8.
Mechanical	Dimensions (H x W x L)	Unpackaged: 3.94 x 1.162 x 5.98 in (10 x 29.5 x 151.86 mm)
	Weight	Unpackaged: 0.60 oz (17 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Box contents	HP USB Dongle Cable, AU / WW Warranty Card, Quick Installation Guide	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad USB Adapter

Host Interface	HP ElitePad docking connector	
Device interface	USB	
Connectors	Signal output: USB female connector	
	Host input: 70-pin male connector	
Supported	Bus Power 5V output	
Operating Temperature	0-40° C (32-104° F)	
Storage Temperature	-10~70° C (14~158° F)	
System Requirements	Software	Windows 8 32-bit
Mechanical	Dimensions (H x W x L)	Unpackaged: 0.43 x 0.85 x 5.08 in (11x 21.5 x 129.11 mm)
	Weight	Unpackaged: 0.49 oz (13.8 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant

Technical Specifications

Box contents	HP ElitePad USB Adapter, documentation
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

HP ElitePad Smart AC Adapter

Host Interface	HP ElitePad docking connector	
Device interface	DC jack	
DC Jack size	7.5 mm	
Connectors	Device output: DC jack female connector Host input: 70-pin male connector	
Supported	Bus Power 5V output	
Operating Temperature	0-40° C (32-104° F)	
Storage Temperature	-10~70° C (14~158° F)	
System Requirements	Software	Windows 8 32-bit
Mechanical	Dimensions (H x W x L)	Unpackaged: 0.87 x 1.38 x 6.13 in (22 x 35.13 x 155.72 mm)
	Weight	Unpackaged: 0.92 oz (26.2 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Box contents	HP ElitePad Smart AC Adapter, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad HDMI & VGA Adapter

Host Interface	HP ElitePad docking connector	
Device interface	HDMI, VGA	
Connectors	Video output: HDMI female/VGA female connector Host input: 70-pin male connector	
Supported resolutions	600 x 800, 768 x 1280, 1024 x 1280, 1680 x 1050, 1920 x 1080	
Operating Temperature	0-40° C (32-104° F)	
Storage Temperature	-10~70° C (14~158° F)	
System Requirements	Software	Windows 8 32-bit
Mechanical	Dimensions (H x W x L)	Unpackaged: 0.551 x 2.56 x 6.02 in (14 x 65 x 152.91 mm)
	Weight	Unpackaged: 1.78 oz (50.4 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Box contents	HP ElitePad HDMI & VGA Adapter, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

Technical Specifications

HP ElitePad Serial Adapter

Host Interface	HP ElitePad docking connector	
Device interface	Serial Port	
Connectors	Device output: RS232 connector	
	Host input: 70-pin male connector	
Supported	Serial port	
Operating Temperature	0-40° C (32-104° F)	
Storage Temperature	-10~70° C (14~158° F)	
System Requirements	Software	Windows 8 32-bit
Mechanical	Dimensions (H x W x L)	Unpackaged: 0.59 x 1.53 x 5.86 in (15 x 38.77 x 148.9 mm)
	Weight	Unpackaged: 0.97 oz (27.4 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Box contents	HP ElitePad Serial Adapter, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

HP ElitePad Ethernet Adapter

Host Interface	HP ElitePad docking connector	
Device interface	RJ45 Ethernet	
Connectors	Device output: RJ45 connector	
	Host input: 70-pin male connector	
Supported	10/100 M	
Operating Temperature	0-40° C (32-104° F)	
Storage Temperature	-10~70° C (14~158° F)	
System Requirements	Software	Windows 8 32-bit
Mechanical	Dimensions (H x W x L)	Unpackaged: 0.62 x 0.96 x 6.65 in (15.75 x 24.39 x 169 mm)
	Weight	Unpackaged: 0.89 oz (25.2 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Box contents	HP ElitePad Ethernet Adapter, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

Technical Specifications

HP ElitePad SD Card Reader

Host Interface	HP ElitePad docking connector	
Device interface	SD connector	
Connectors	Device output: SD connector	Host input: 70-pin male connector
Supported	SD card	
Operating Temperature	0-40° C (32-104° F)	
Storage Temperature	-10~70° C (14~158° F)	
System Requirements	Software	Windows 8 32-bit
Mechanical	Dimensions (H x W x L)	Unpackaged: 0.35 x 1.34 x 1.81 in (9 x 34 x 46 mm)
	Weight	Unpackaged: 0.45 oz (12.8 g)
Environmental	EMC	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	RoHS	RoHS Compliant
Box contents	HP ElitePad SD Adapter, documentation	
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet	

Input/Output

HP Slim Bluetooth Keyboard

Dimensions (H x L x W)	0.6 x 10.3 x 4.6 in (17.1 x 264 x 116.8mm)
Weight	9.5 oz (270 g)
Operating distance	32.8 ft (10.0 m) with no obstructions
System requirements	Windows Vista, Windows 7, Windows 8; Bluetooth®-enabled PC
Kit contents	HP Slim Bluetooth Keyboard, two AAA batteries, documentation
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

Technical Specifications

HP Executive Tablet Pen G2

Dimensions (H x L x W)	5.65 x 0.47 in (143.5 x 11.8 mm)
Weight	1.06 oz (30 g)
Color	Black
Power	One AAA battery
System requirements	Windows 8, Windows 8.1
Kit contents	HP Executive Tablet Pen G2, AAA battery and documentation
Functionality	Right-click, draw, type, and navigate better than ever with a capacitive tip that offers pin-point accuracy to help improve productivity. Pen supports hover feature and pressure sensitivity levels up to 256 Windows 8 Certified Soft tip for quiet performance and more precise writing capabilities
Compatibility	HP ElitePad 1000 G2 Tablet, HP EliteBook Revolve 810 G2

Cases

HP ElitePad Leather Slip Case

Dimensions	10.75 x 9 x 0.75 in (273.05 x 228.60 x 19.05 mm)
Weight	0.50 lb (226g)
Kit contents	HP ElitePad Leather Slip Case
Compatibility	HP ElitePad 900 G1 Tablet, HP ElitePad 1000 G2 Tablet

HP ElitePad Case

Dimensions	14.71 x 10.5 x 0.50 in (373.73 x 268.16 x 13.00 mm)
Weight	0.50 lb (226 g)
Kit contents	HP ElitePad Case
Compatibility	HP ElitePad 900 G1 Tablet , HP ElitePad 1000 G2 Tablet

HP ElitePad Rugged Case

Dimensions	10.86 x 7.59 x 0.90 in (275.85 x 192.71 x 22.95 mm)
Weight	1.32 lb (600 g)
Kit contents	HP ElitePad Rugged Case, stand, hand strap, shoulder strap, documentation
Compatibility	HP ElitePad 900 G1 Tablet

Technical Specifications

HP ElitePad Rugged Case G2

Dimensions	10.86 x 7.59 x 0.90 in (275.85 x 192.71 x 22.95 mm)
Weight	1.32 lb (600 g)
Kit contents	HP ElitePad Rugged Case, stand, hand strap, shoulder strap, documentation

Compatibility

Each HP ElitePad Expansion Suite accessory included in this QuickSpecs is compatible with the HP ElitePad 900 G1 and ElitePad 1000 G2 Tablet.

Service and support

Each accessory carries a one-year limited warranty. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.

Copyright © 2014 Hewlett-Packard Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All other trademarks are the property of their respective owners.