

Data Sheet

FUJITSU Display P24-8 WE Neo

Ergonomic Widescreen 61.1 cm (24.1 inch) Versatile Display
With Advanced Sensor for a Secure Workplace

The FUJITSU Display P24-8 WE Neo is a 16:10 IPS panel monitor that has DisplayView™ IT Suite that helps you activate features such Presence Sensor, Workplace Lighting Guide that promote the overall ergonomics and security of your workplace. The monitor has a 178°/178° wide viewing angle delivering a consistent picture quality and is ideal for CAD and Document Management applications.

High performance 16:10 IPS monitor with 1920 x 1200 resolution that delivers consistent clarity from any perspective

Enhance productivity with ergonomic features like Auto Brightness Control, Workplace Lighting Guide using our DisplayView™ IT Suite

Prevent unauthorized personnel from accessing confidential data by securing your workplace with our Presence Sensor technology

Ultra-thin bezel housing on three sides that allows bi-directional 90° orientation with Auto Pivot Sensor making it ideal for power users

High precision pre-calibrated monitor delivering 100% sRGB and a DICOM preset mode making it ideal for clinical review applications

5-in-1 stand base with cable guide that enables you to have a clean workspace and also adjust monitor height, tilt, swivel, rotate picture as per requirement

Ideal choice for multi monitor environments due to DisplayPort 1.2 and DisplayPort output that enables Daisy Chaining



Technical details

Special features

Presence sensor with PC security solution, In-Plane Switching (IPS) technology, DICOM Greyscale Standard Display Function compatible gamma preset, Color accuracy average DeltaE<2, Eco button, 5-in-1 Stand, Auto Brightness Control (ABC), Workplace Lighting Guide, Auto Pivot, Always available USB (in operating and standby mode), DisplayView™ IT Suite, 24/7 usage, Cable guide, Integrated speakers

Ergonomic stand

| | |
|--------------------------------|---|
| Stand | 5-in-1 Stand |
| Height adjust range | 130 mm |
| Picture height over desk (min) | 40 mm |
| Rotation to portrait | 90° clockwise and counterclockwise, Auto Pivot sensor |
| Tilt angle | -5° / +35° |
| Swivel angle | 345° |

Picture performance

| | |
|------------------------------------|---|
| Panel and backlit | In-Plane Switching (IPS) technology/LED |
| Screen Surface Treatment | 3H hard coating, Anti-glare |
| Contrast - typical | 1000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time gray to gray typical | 5 ms (in Video mode) |
| Viewing angle (h/v) - typical | 178°/178° CR10:1 |
| Color performance | 16.7 million colors |
| High color gamut - typical | 77% NTSC / 100% sRGB color space |
| Brightness - typical | 300 cd/m ² |

Size and resolution

| | |
|---------------------------|---|
| Aspect ratio | 16:10 |
| Diagonal Size | 61 cm (24-inch) |
| Resolution (native) | 1,920 x 1,200 pixel |
| Resolution (interpolated) | 1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 1,200 pixel, 1,400 x 900 pixel, 1,280 x 800 pixel, 1,280 x 768 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel |
| Picture size | 518 x 324 mm |
| Pixel Pitch | 0.270 mm |

Frequencies

| | |
|------------|-------------|
| Horizontal | 30 - 82 kHz |
| Vertical | 48 - 76 Hz |

Connectivity

| | |
|---------------------|--|
| DisplayPort | 1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2 |
| HDMI | 1 x HDMI 1.4 |
| DVI | 1 x DVI-D (HDCP) |
| Audio signal output | 3.5 mm stereo phone jack for head phone |
| Audio sound output | 2 x 2 W |
| USB downstream | 4 x USB 3.1 Gen1 |
| USB upstream | 1 x USB 3.1 Gen1 |

Ease-of-use menu

| | |
|-----------------------|---|
| Notes | 6 sensor keys on front side |
| Direct Access Keys | Brightness, ECO, Input, Mode, Audio, Menu |
| Languages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto level, Auto Brightness, ACR, Lighting Guide |
| Mode | D-Mode, sRGB, Office, Photo, Video, Low Blue Light, Custom |
| Color | 5000K, 6500K, 7500K, Native, RGB Adjust |
| Image adjust | Expansion, Saturation, Sharpness |

| | |
|--|--|
| Audio | Mute, Volume |
| Information | Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status, ABC Status |
| Advanced settings | Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/CI, Factory Recall |
| Power consumption (typical) | |
| Soft switch off | 0.2 W |
| Power save mode | 0.3 W |
| Operating with EPA settings | 14.4 W |
| Total Energy Consumption (ETEC) | 46 kWh/year |
| Operating maximum brightness | 25 W |
| Power supply | integrated |
| Power notes | Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 7.0 |
| Electrical values | |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Protection class | 1 |
| Compliance | |
| Europe | Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration |
| Model | P24-8W |
| Germany | TÜV GS |
| Russia | EAC |
| USA/Canada | FCC Class B, cUL |
| Australia/New Zealand | (on customer request) |
| Japan | VCCI |
| South Korea | KC#E-Standby |
| Singapore | S-Mark |
| Taiwan | BSMI |
| China | CCC |
| Saudi Arabia | SASO |
| Global | TCO Certified Displays 7.0, ENERGY STAR® 7.0, EPEAT® Gold (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Flicker Free Certified, TÜV Low Blue Light Certified |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Dimensions / Weight / Environmental | |
| Dimension without stand (W x D x H) | 531.8 x 56 x 350 mm |
| | 20.94 x 2.20 x 13.78 inch |
| Dimension with stand (W x D x H) | 531.8 x 212.7 x 367.7 mm |
| | 20.94 inch x 8.37 x 14.48 inch |
| Weight (packed) | 8.07 kg |
| | 17.79 lbs |
| Weight (unpacked) | 5.82 kg |
| | 12.83 lbs |
| Weight (Monitor only) | 3.8 kg |
| | 8.38 lbs |
| Operating ambient temperature | 5 - 35 °C |
| Operating relative humidity | 10 - 85 % (non condensing) |
| Miscellaneous | |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared |
| Color | Marble grey |

Package content

| | |
|--------------------------------------|---|
| Display delivered accessories | DisplayPort data cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes |
|--------------------------------------|---|

| | |
|--|--|
| Display delivered accessories notes | Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for AutoPivot function and Presence Sensor PC security solution |
|--|--|

Order information

| | |
|-------------------|-------------------|
| Order Code | S26361-K1647-V140 |
|-------------------|-------------------|

| | |
|-----------------|---------------|
| EAN Code | 4059595443088 |
|-----------------|---------------|

Warranty

| | |
|------------------------|--------------------------------|
| Warranty period | 3 years (depending on country) |
|------------------------|--------------------------------|

| | |
|----------------------|---|
| Warranty type | Collect & Return Service (depending on country specific requirements) |
|----------------------|---|

| | |
|--|---|
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
|--|---|

| | |
|---------------------------------|-----------------------------------|
| Spare Parts availability | 5 years after end of product life |
|---------------------------------|-----------------------------------|

| | |
|------------------------|---|
| Service Weblink | http://www.fujitsu.com/fts/services/support |
|------------------------|---|

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display P24-8 WE Neo , Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display P24-8 WE Neo , please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



**Green
Policy
Innovation**

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-02-06 EM-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH