

Plug (1) IEC 60309 32A



Cable Length (m) 3
Voltage 230V
Current 32
Current Monitoring Yes
Phase Single-phase
Frequency 50Hz

Output

Grip cable retention Yes
(20) IEC-320-C13



Outlets (4) IEC-320-C19



Circuit Breakers 2 single pole
Outlet Control No

Protection & Filtering

Spike/Surge Suppression None
EMI/RFI Filter None

Control & Interface

Daisy Chain 8 ePDUs
Operating Temperature 60 Degrees C
Hot Swap Network and Control Yes
Communication and Protocols HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
Optional Temperature and Humidity probe EMP001
Environmental Interface Yes
Serial Interface Yes
Ethernet Interface Yes

Voltage Monitoring Yes

Metering and Switching

Metering Input, Branch, Phase

Metering Characteristics V, W, A and kWhr, Active power, Apparent Power, Peak Power

Metering Accuracy IEC Class 1 Billing grade Accuracy

Environmental & Approval Standards

Approvals CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011 Safety - Part 1: General Requirements, IEC 60950-1(ed.2), IEC 60950-1(ed.2);am1
EN 55022:2010 Radio Disturbance characteristics - Limits and methods of measurement. EN 55024:2010 Immunity characteristics - Limits and methods of measurement.

Electromagnetic compatibility EN 61000-6-2:2005 Part 6-2: Generic standards - Immunity for industrial environments EN 61000-6-4:2007+A1:2011 Part 6-4: Generic standards - Emission standard for industrial environments

Environmental RoHS Directive – 2011/65/EU, EN 50581 : 2012, REACH Regulation (CE No. 1907/2006), WEEE directive 2012/19/EU, PEP ecopassport (Basic ePDUs) Packaging: 100% recycled, 100% recyclable: no plastic, no metal, no foam.

Manufacturing Plant ISO 9001:2008 / ISO 14001:2004

Warranty

Standard warranty 2 years

- [Privacy Policy](#)
- [Terms & Conditions](#)
- [Copyright](#)

- © 2020 Eaton
All Rights Reserved

