

# HS-1600T Mark II Specifications

HS-1600T MKII 4-Channel HD/SD HDBaseT Portable Video Streaming Studio	
Video Standard	HD & SD
Video Format	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz
Input Routable / Crosspoint	N/A
Video Inputs	3 x HDBaseT 1 x HDMI
Computer Graphic Interface	1 via HDMI
Down-converted Output	Yes
Video Outputs	2 x HDMI PGM 1 x HDBaseT (RJ-45) 1 x Stream Port (RJ-45)
Audio Inputs	2 x Balanced XLR 1 x Stereo RCA (L/R) De-embedded Digital Audio
Audio Output	1x Stereo headphone
Digital Embedded Audio Support	Input 2 channels Output 2 channels
Audio Delay Calibration	N/A
A+V Switching	N/A
USK	1x USK Lumakey support
DSK	N/A

Picture in Picture	1
Logo Insertion	N/A
Built-in Audio Mixer	4 channels
Built-in Monitor Display	17.3" HD TFT LED Backlit 1920x1080 pixels
Built-in Intercom & Tally	N/A
Streaming Video Encode	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
Streaming Audio Encode	AAC-LC Configurable bit rate ranging from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
Streaming Protocol	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP RTMP/RTMPS (Publish)
Streaming Control	Web UI for system configuration and control
Recording File System	FAT, exFAT, NTFS
Recording File Format	MP4
Recording Setting Control	Web UI for system configuration and control
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	17.2 Lbs (7.8 kg), Reinforce Plastic Case
Power	DC 48V, 4.16A
Operating Temp. Range	0~40 °C
Optional Accessories	CB-60/61/62
<b>What's in the Box</b>	
Content	1 x HS-1600T Mark II Product 1 x AD Switch DC 56V with AC Cord 1 x Thank You Card 3 x Ethernet Cables (55in. / 140cm)

**Special Notes**

Cable Requirement

Requires Solid Core, Cat -6 Shielded cable for Ethernet connection