

65&90w POE injector

POE Injector support "IEEE 802.3af/at/bt" "POE++" POE supply;



Main Features

- ◆ 2 port Gigabit Rj45 network, 1GE POE out+1GE data input
- ◆ Support Spherical camera, Industrial wireless AP etc.
- ◆ Fluid Control: Full-duplex: IEEE 802.3x, Half-duplex: back pressure.
- ◆ Auto MDI/MDIX.
- ◆ Support port lightning protection.
- ◆ Store-and-forward.
- ◆ All ports support wire speed switch, jumbo frame transmission.
- ◆ Plug and play, self-adaption.

Specification

Model	20103210	20103211
Power pin	12+/45+ 36-/78-	12+/45+ 36-/78-
POE out	52V 1.25A	55V 1.63A
Power	65W	90W
POE	IEEE802.3af/at/bt POE++	
Data pin	12364578	
Power input	AC 100-240V 50/60HZ	
Shell	Metal case	
Port	1GE POE output+1GE data input	
Function	Plug and Play, without configuration management Under-voltage, over-voltage, over current short circuit protection System Reliability: MTBF>100k hours Comply to EN55022, CLASS BCE&RE	
Environmenta	Working Temperature: 0°C~40°C Storage temperature: -40°C~80°C	
	Working Humidity: 10%~90% RH non-condensing	

	Storage Humidity: 5%~90% RH non-condensing
Speed	Ethernet 10Mbps half-duplex, 20Mbps full-duplex Fast Ethernet 100Mbps half-duplex, 200Mbps full-duplex Gigabit Ethernet 2000Mbps full-duplex
Network Media	10Base-T: Pair 2 Category 3(cat 3) and above UTP/STP(≤150m) 100Base-TX: Pair 2 Category 5(cat 5) and above UTP/STP(≤150m) 1000Base-T: Pair 4 Category 5(Cat5e) and above UTP/STP(≤150m)
Product Size	182mm*72mm*39mm(L*W*H)
Weight	0.9Kg

Product Information

Model Number: 20103210 resp. 20103211

Product Details: 1GE POE out+1GE data input



DIREKTRONIK

Direktronik AB tel. 08-52 400 700 www.direktronik.se