

DeckLink Studio 4K



\$595

If you work with a wide range of analog video and audio gear, and need to move seamlessly between SD, HD, 2K and Ultra HD, then DeckLink Studio 4K is perfect! DeckLink Studio 4K includes a massive number of analog and digital video connections including SD/HD/Ultra HD 6G-SDI, HDMI 1.4b, SD/HD component, composite, S-video, 4 ch balanced analog audio, 2 ch AES/EBU switchable to 6 ch out, Black Burst and Tri-Sync reference input, RS-422 deck control connections, keying in SD and a hardware down converter. Perform editing, paint and broadcast design and more with the ultimate future proof design!

Connections

SDI Video Inputs

1 x 10-bit SD/HD/2K/4K. Supports 6G 4:2:2 and 3G 4:4:4.

SDI Video Outputs

1 x 10-bit SD/HD/2K/4K. Supports 6G 4:2:2 and 3G 4:4:4.

Analog Video Inputs

1 x Component YUV on 3 BNCs, 1 x Composite, 1 x S-Video. Component supports HD and SD.

Analog Video Outputs

1 x Component YUV on 3 BNCs, 1 x Composite, 1 x S-Video, 1 x SD-SDI. Component supports HD and SD.

Analog Audio Inputs

4 Channels of professional balanced analog audio via 1/4 inch jack connectors.

Analog Audio Outputs

4 Channels of professional balanced analog audio via 1/4 inch jack connectors. Channels 3 & 4 can switch to AES/EBU outputs.

AES/EBU Audio Inputs

2 Channels unbalanced with sample rate converter.

AES/EBU Audio Outputs

2 Channels unbalanced. Analog outputs 3 and 4 can switch to AES/EBU outputs for audio 3 & 4 and 5 & 6 output. This provides a total of 6 AES/EBU output audio channels when using this feature.

SDI Audio Inputs

16 Channels embedded in HD/2K/4K.
8 Channels embedded in SD.

SDI Audio Outputs

16 Channels embedded in HD/2K/4K.
8 Channels embedded in SD.

HDMI Video Inputs

1 x HDMI type A connector.

HDMI Video Outputs

1 x HDMI type A connector.

HDMI Audio Inputs

8 Channels embedded in SD, HD, 4K.

HDMI Audio Outputs

8 Channels embedded in SD, HD, 4K

Sync Input


Tri-Sync or Black Burst.

Device Control

Sony™ compatible RS422 deck control ports. Serial ports TxRx direction reversible under software control.

Computer Interface

PCI Express 4 lane generation 2, compatible with 4,8 and 16 lane PCI Express slots.



Supported Codecs

AVC-Intra, AVCHD, Canon XF MPEG2,
Digital SLR, DV-NTSC, DV-PAL,
DVCPRO50, DVCPROHD, DPX, HDV,
XDCAM EX, XDCAM HD, XDCAM
HD422, Apple ProRes 4444, Apple
ProRes 422 HQ, DNxHR & DNxHD,
Apple ProRes 422, Apple ProRes LT,
Apple ProRes 422 Proxy,
Uncompressed 8-bit 4:2:2,
Uncompressed 10-bit 4:2:2,
Uncompressed 10 bit 4:4:4.

Software

Software Included

Media Express, Disk Speed Test,
LiveKey, Blackmagic Desktop Video
Utility and Blackmagic driver on Mac
OS and Windows. Media Express,
Blackmagic Desktop Video Utility and
Blackmagic driver on Linux.

Internal Software Upgrade

Firmware built into software driver.
Loaded at system start or via updater
software.

Physical Installation

PCI Express 4 lane generation 2,
compatible with 4, 8, 16 lane PCI
Express slots on Mac OS, Windows
and Linux. Please check the Support
pages to see the full system
requirements.

Software Applications



DaVinci Resolve



Fusion



Final Cut Pro X



Adobe Premiere Pro CC



Avid Media Composer



Adobe After Effects CC



Avid Pro Tools



Steinberg Cubase



Autodesk Smoke



Adobe Photoshop CC

Other supported applications include: The Foundry Nuke, Grass Valley Edius, Steinberg Nuendo, Sony Catalyst Production Suite, Tools On Air Just: Play & Live & In, Softron MovieRecorder & MReplay, Adobe Flash Media Live Encoder, Telestream Wirecast, Livestream Producer, Resolume Arena, Magix Vegas Pro & Movie Edit Pro Premium, Corel VideoStudio Pro, CyberLink PowerDirector, Vidblaster X & Studio & Broadcast, Uniplay One & CG, CasparCG Server, Magicsoft CG, Xsplit Broadcaster, Imagine Communications Velocity & InfoCaster, DevTek Easy Media Suite, Metus Ingest, Boinx Software MimoLive, Cinegy Capture Pro, vMix Live, Renewed Vision ProPresenter, Ventuz Director, Class X Liveboard & Coral CG, Glookast Capturer, Open Broadcaster Software Studio, Nautilus NEMO3D, Burst Video WebClip2Go & [REC]Marker, Autodesk Flame.

Video Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60

1080p24, 1080p25, 1080p29.97,

1080p30, 1080p50, 1080p59.94,

1080p60

1080PsF23.98, 1080PsF24,

1080PsF25, 1080PsF29.97, 1080PsF30

1080i50, 1080i59.94, 1080i60

2K Video Standards (SDI Only)

2K DCI 23.98p, 2K DCI 24p, 2K DCI

25p

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,

2160p29.97, 2160p30

4K Video Standards

4K DCI 23.98p, 4K DCI 24p, 4K DCI

25p*

* SDI Only

SDI Compliance

SMPTE 292M, SMPTE 259M, SMPTE

296M, SMPTE 372M, SMPTE 425M,

SMPTE 2081, ITU-R BT.656 and ITU-R

BT.601.

SDI Metadata Support

RP 188/SMPTE 12M-2 and closed

captioning.

SDI Video Sampling

4:2:2, 4:4:4*

*4K is 4:2:2.

SDI Color Precision

8, 10-bit RGB 4:4:4 in all modes up to

1080p25 2K DCI, 8, 10-bit YUV 4:2:2 in

all modes.

Color Space

REC 601, REC 709

HDMI Video Sampling

4:4:4, 4:2:2 & 4:2:0

HDMI Color Precision

10-bit RGB HD

10-bit YUV in HD and 4K

HDMI Configuration

HDMI 1.4b. Automatically configures

to connected display.

Audio Sampling

Television standard sample rate of 48 kHz at 24 bit.

Color Precision

10-bit

Color Space

REC 601, REC 709

HDMI Resolution

Pixel for pixel up to 4K resolutions.

Multiple Rate Support

HDMI and SDI video connections are switchable between SD/HD/2K and UHD. Component analog video connections are switchable between SD and HD.

Copy Protection

HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

Processing**HD Down Conversion**

Built in, high quality hardware down converter outputs HD-SDI on SDI output, SD on SD-SDI, Composite and S-Video outputs when working in HD video formats on playback. Switch analog video to Component and choose HD or SD output. Selectable between letterbox, anamorphic 16:9 and center cut 4:3 styles.

HD Up Conversion

Software based up conversion from SD to 720HD or 1080HD on capture. Selectable between 4:3 pillarbox, 14:9 pillarbox and 16:9 zoom.

Cross Conversion


Software based cross conversion from 720HD to 1080HD and 1080HD to 720HD on playback.

Real Time Effects

DaVinci Resolve, Final Cut Pro X internal effects. Adobe Premiere Pro CC Mercury Playback Engine effects. Avid Media Composer internal effects.

Colorspace Conversion

Hardware based real time.

Physical Specifications

Operating Systems



Mac 10.14 Mojave,
Mac 10.15 Catalina or later.



Windows 8.1 and 10, all 64-bit.



Linux

Power Requirements

Power Consumption

22 Watts

EMC Certifications

FCC, CE and C-Tick

Environmental Specifications

Operating temperature

5° to 40° C (32° to 104° F)

Storage temperature

-20° to 45° C (-4° to 113° F)

Relative Humidity

0% to 90% non-condensing

What's Included

DeckLink Studio 4K
SD card with software and manual
Breakout cable for analog and RS-422 control.
HDMI bracket

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2020, all rights reserved.
All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs.
This website uses remarketing services to advertise on third party websites to previous visitors to our site.
You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller