# **GSX 1000**

### Audio amplifier

The GSX 1000 Audio Amplifier is a dynamic gaming amplifier with HD Audio and 7.1 surround sound modes, and separate audio and communication control. Designed for the gamer seeking enhanced audio to better enjoy their games, the amplifier delivers exceptional bass performance, acoustic clarity and precise positional audio cues for an immersive game experience.

Intuitive design of the LED touch panel and volume ring allow for quick fingertip control of your sound. Adjust game and chat audio separately and even control the loudness of your own voice in the headset

Compatible with both the PC and Mac® with all 2-jack analog headsets, a built-in DAC and EQ presets serve the gamer as well as the movie lover. Four profile settings allow you to personalize and save your favorite audio settings.

See more at eposaudio.com/gsx-1000





### Key benefits & features

#### Binaural Rendering Engine - 7.1 surround

Delivers exceptional immersion with enhanced audio performance

#### Dedicated built in DAC

Get precise control of your sound with a dedicated DAC chip

#### Presets - story, esports, music, off

Specially attuned settings focus sound frequencies where they are needed

### Separate control for game audio and chat

Cut through the noise for game chat when needed for on-the-fly strategizing

#### Sidetone

Adjust the loudness of your own voice in your headset.

## EPOS | SENNHEISER

# GSX 1000

## Product data

General		
USB standard	USB 2.0 full speed & USB audio 1.0	
Total harmonic distortion	0.005 % THD @ -3dBFS	
Cable length	1.2 m	
Connector plugs	3.5 mm headset socket 3.5 mm microphone socket 3.5 mm loudspeaker socket mini-USB socket	
Compatibility	PC & Mac®	
Warranty	2 years, international	
Supported sample rates		
Main Audio	7.1: 44.1 kHz @ 16 bit 7.1: 48.0 kHz @ 16 bit 2.0: 44.1 kHz @ 16 bit 2.0: 48.0 kHz @ 16 bit	
Main Audio HD	2.0: 96.0 kHz @ 24 bit	
Communication Audio	1.0: 16.0 kHz @ 16 bit	
Audio outputs		
Headphones  - Frequency response  - Recommended headphone impedance  - Max. output voltage	DC coupled & dual rail power supply O - 48.0 kHz 16 - 150 $\Omega$ 1 V RMS @ 32 $\Omega$	
Line out (AUX)  - Frequency response  - Max. output voltage	1.5 Hz - 48.0 kHz 1 V RMS @ 10 Ω	

Packaging		
Dimension of product packaging (L x W x H)	150 x 70 x 145 mm	
Package weight (incl. complete product and packaging)	389 g	
Dimension of master carton (L x W x H)	420 x 360 x 165 mm	
Units in distributor master carton	10	
Languages	English, German, French, Spanish, Italian, Dutch and Portuguese	
Content of delivery		
What's in the box	USB cable, Quick Start Guide, Safety Guide	

# GSX 1000

## Product overview

Product	Art. no.	Description	EAN / UPC code
GSX 1000	1000237	USB audio amplifier for gaming	EAN: 57 14708 00038 9 UPC: 8 40064 40038 1

