0100 E0 00 - 11-10 - 1

IPC 4U-4416





IPC 4U-4416

The **IPC 4U-4416** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 4U-4416** offers the possibility to install sixteen 2.5" or 3.5" Hot-Swap HDDs, two 5.25" external drives or eight internal 2.5", alternatively 3.5" HDDs.

The **IPC 4U-4416** has five fans as standard, from which are three 120mm fans are mounted directly at the back of the drive brackets. In addition, two 80mm fans at the back ensure a reliable and optimal cooling.



IPC 4U-4416

<u>pecifications</u>	
Motherboard	Mini ITX, μΑΤΧ, ΑΤΧ, eATX, SSI EE
	maximale motherboard size WxD: 305mmx345mm, 12" x 13.5
Max. Drive Bays	2.5" or 3.5" external Hot-Swap (max. 12G): 1
	2x Drive Bays for 1x 5.25" external or 1x 3.5" internal or 4
Front Connectors	2.5" internal hard drive/ USB 3.0:
Front Connectors	USB 3.0: USB 2.0:
Cooling System	Internal: 3x 120mr
Cooling System	(included, Molex connector, hot pluggabl
	Rear: 2x 80mr
	(included, Molex connecto
	Front: 4x 40mr
Controls	Power-Butto
	Reset-Butto
LED	Powe
	HDD Activit
	3x Network Activit
	Ale
Power Supply	ATX / Redundant PS
Material	1.0-1.2mm Ste
Maximum CPU cooler height	155mı
Maximum graphics card length	345mi
Packing Units	Shipping Unit: 1 piec
Overstand Allerman	Pallet: 14 piece
Guarantee and Warranty	Case 24 Months Warrant
Article Number EAN-Code	8888712 426013312641
Scope of Delivery	426013312641 Screw se
Scope of Delivery	Mounting bracket for ATX (preassembled), 4U redundant an
	3U triple redundant PS
	Adapter for 2U PSU + optional 80mm fan bracke
	Angle bracket for diverse PS
	Assembly to
Features	2x 80mm fan and 3x 120mm fan include
	(3x 120mm fan hot pluggabl
	Drive brackets removable
	USB 3.0 and USB 2.0 as block connecto
	Hot-Swap backplane with SFF-8087 socket

HOT-SWAP DACKPIANE WITH SITE 6007 SETTING THE BACKPIANE IS ON SETTING TO THE BACKPIANE IN OPERATION OF THE BACKPIANE AND ASSOCIATION OF THE BACKPIANE AND ASSOCIATION



IPC 4U-4416

Dimensions and Weight Cage Case Package Height 178mm 178mm 250mm Width 433mm 481mm 560mm Depth 650mm 688mm 835mm Weight (net): 15.14kg Weight (gross): 17.73kg

ower Supply	Ĺ	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	41
PCI-Express 6+2Pin	4160	
PCI-Express Cin	tho	9
IDE 4Pin		-
S-ATA		-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification: