



Feature:

- (1) No additional power supply or battery, Fast Ethernet detect whether with power;
- (2) Identification of Mid-Span (4/5 7/8) and End-Span (1/2 3/6);
- (3) Detectable IEEE802.3 af / at PoE standard and passive PoE;
- (4) The detector includes a male and female interface for direct detection of PoE interfaces
- (5) Dual LED indicates the obvious intuitive;
- (6) 8cm extension cable network to meet the intensive probe interface;
- (7) Overvoltage protection 63V, reliable products;
- (8) Gold-plated 30u flat pin RJ45, increase the contact surface,

Item		Description
PoE Power	Power Supply	Passive
	Input Power	DC 24V-60V
Port	Ethernet Port	1×RJ45 Female Port , 1×RJ45 Male Port
	PoE Standard	IEEE802.3af/at and Passive PoE
	Pairs Testing	1/2 3/6 4/5/7/8
	Max Voltage Pressure	DC 63V
Status	LED Indication	Yellow Light for PoE End-Span Green Light for Light PoE Mid-Span Brilliant is Standard PoE Flash is Passive PoE
Operating Environment	Working Temperature	-10°C~55°C
	Storage Temperature	-40°C~85°C
	Humidity (non-condensing)	0~95%
Physical Properties	Dimension (L×W×H)	41mmX24.5mmX21.6mm
	Material	ABS Plastic
	Colour	Black
	Weight	20g

SCENARIO



Cat5e/6

- (1) If the port have PoE (Af/At Standard), The product Yellow Light will Flash,
- (2) If there is PoE+ (60W Standard), The Product Green Light will on.
- (3) If There is not PoE Standard, The product LED light will off