

TeraStation™ 5010

Network Attached Storage



NAS with native 10GbE connectivity.

Scalable high performance network storage for businesses.

Buffalo's TeraStation™ 5010 series has been built for small and medium sized businesses seeking an easy and cost-effective 10GbE platform. The TS5010 is a network attached storage (NAS) solution with iSCSI protocol designed to move SMB data at enterprise level speeds and eliminate the bottlenecks that can occur on slower networks.

Thanks to its powerful hardware the TS5010 series can run multiple concurrent services seamlessly with minimal performance degradation, and is ideal for organizations looking to add an affordable virtualized storage to their business network. Branch offices no longer need full-scale server infrastructure for simple tasks such as file sharing and backup.

In combination with Buffalo's 10GbE business switches the quad core processor featuring TS5010 reaches faster than ever data transfer speeds. The series comes populated with NAS- or enterprise nearline (TS51210RH) grade HDD and is available in 2-,4- or 8-bay desktop and 4- or 12-bay rackmount configurations.

The 8- and 12-bay versions come fully populated or partially populated with four hard drives, thus giving companies the flexibility to start with a smaller initial investment and increase the total capacity when the need arises in the future. The 2-bay TS5210DF is equipped with SSDs and therefore highly shock-/vibration-proof and extremely fast.

Features and Benefits

- High-speed native 10GbE connection (1 or 2 (TS51210RH only) 10GbE ports)
- 2.5/5Gbps compatible, compliant with NBASE-T (IEEE 802.3bz) standard
- Powered by the high performance Annapurna Labs® Quad-Core processor with 4GB/8GB (TS51210RH) DDR3 ECC RAM
- Available in 2-bay, 4-bay and 8-bay desktop models or 4-bay and 12-bay rackmount
- Simultaneous NAS and iSCSI target functionality
- Advanced NTFS Permissions (Windows ACL)
- VMware ready
- Rapid RAID mode change
- RAID Mode Manager

- TRIM Command for increased SSD life time (TS5210DF)
- AES 256bit data encryption
- Boot Authentication ensures the device is only accessible on authorized networks
- Integrated cloud backup with Dropbox, Dropbox Business and Amazon S3; remote access through WebAccess
- NovaBACKUP® backup software (11 licences for NovaBACKUP® Buffalo Edition)
- Duplex System Firmware Boot
- Active Directory (up to 10.000 supported users/groups imported from the domain)
- 3 year standard warranty (5 years for TS51210RH) including 24-hour HDD replacement; warranty extensions available separately (not for TS51210RH)

About BUFFALO

BUFFALO is a leading global provider of award-winning storage, networking and multimedia solutions for the home and small business environments as well as for system builders and integrators. With more than four decades of networking and computer peripheral experience, BUFFALO has proven its commitment to delivering innovative solutions that have put the company at the forefront of infrastructure technology.

Specifications

Models	TS5210DF (2-bay)	TS5210DN (2-bay)	TS5410DN (4-bay)	TS5410RN (4-bay)	TS5810DN (8-bay)	TS51210RH (12-bay)	
Part Numbers	TS5210DF00502-EU TS5210DF0202-EU	TS5210DN0402-EU TS5210DN0602-EU TS5210DN0802-EU TS5210DN1202-EU TS5210DN1602-EU	TS5410DN0804-EU TS5410DN1204-EU TS5410DN1604-EU TS5410DN2404-EU TS5410DN3204-EU TS5410DN0802-EU TS5410DN1602-EU	TS5410RN0804-EU TS5410RN1204-EU TS5410RN1604-EU TS5410RN2404-EU TS5410RN3204-EU	TS5810DN1604-EU TS5810DN3204-EU TS5810DN3208-EU TS5810DN6408-EU	TS51210RH0804-EU TS51210RH1604-EU TS51210RH3204-EU TS51210RH4004EU TS51210RH42412-EU TS51210RH4812-EU TS51210RH9612-EU TS51210RH9612-EU TS51210RH12012EU	
Configuration	Desktop	Desktop	Desktop	Rackmount 19" 1U	Desktop	Rackmount 19" 2U	
Total Capacities	512 GB, 2 TB	4, 6, 8, 12, 16 TB	8, 12, 16,	, 24, 32 TB	16, 32, 64 TB	8, 16, 24, 32, 40, 48, 96 120 TB	
Anti-Vibration	10-150Hz 6G						
nternal Hard Drives							
Гуре	SSD			HDD		Nearline HDD	
Number of Drives	2	2	4 (fully populated) 2 (partially populated)	4	8 (fully populated) 4 (partially populated)	12 (fully populated) 4 (partially populated)	
Capacities	256 GB, 1 TB		2, 3, 4, 6, 8 TB		4, 8 TB	2, 4, 8, 10 TB	
Orive Interface			SATA	6 Gbps			
Supported RAID	JBOD/0/1 JBOD/0/1/5/6/10						
USB Interface							
Standard Compliance			USB 2	2.0/3.0			
Connector Type			At	type			
Number of Ports	i i					2 x USB 2.0, 2 x USB 3	
Data Transfer Rates		480 Mbps / 5 Gbps					
System / Performance							
CPU		An	napurna Labs® Alpine-Prozes	ssor AL314 (1.7 GHz Quad	d-Core)		
RAM		4 GB DDR3 with ECC 8 GB DDR3 with ECC					
Environmental & Power							
Power Unit	1	1	1	1	1	1 (2nd optional)	
Power Consumption	Max. 85 W; average active: 30 W; average idle: 15 W; standby: 0.8 W	Max. 85 W; average active: 45 W; average idle: 32 W; standby: 0.8 W	Max. 85 W; average active: 56 W; average idle: 45 W; standby: 0.8 W	Max. 100 W; average active: 60 W; average idle: 46 W; standby: 0.7 W	Max. 150 W; average active: 108 W; average idle: 87 W; standby: 4.5 W	Max. 500 W; average active: 122 W; average idle: 100 W; standby: 3.9 W	
Power Supply	Internal AC 100-240 V, Universal 50/60 Hz						
Operating Temperature	0° - 40°C						
Operating Humidity	10 - 85 % non-condensing						
Dimensions/Weight							
Dimensions (WxHxD)	170 x 170 x 230 mm	170 x 170 x 230 mm	170 x 215 x 230 mm	430 x 44,3 x 430 mm	300 × 215 × 230 mm	481 x 88 x 736.9 mm	
Weight	3.5 kg	4.8 kg	7 kg	8.4 kg	12.5 kg	20 kg (main unit with 4 HDDs) 25 kg (main unit with 12 HDDs)	
						12 11000)	
.AN Interface							
	(10BASE-T) IEEE802.3, (100BASE-TX	() IEEE802.3u, (1000BASE-T)	 IEEE802.3ab, (10GBASE-	-T) IEEE802.3an, (NBASE-T		
Standards Compliance	(10BASE-T) IEEE802.3, (100BASE-TX	() IEEE802.3u, (1000BASE-T) 1 (10GBASE-T), 2 (1GBASE-		-T) IEEE802.3an, (NBASE-T		
Standards Compliance Number of Ports	(10BASE-T) IEEE802.3, (100BASE-TX	1 (10GBASE-T), 2 (1GBASE-		-T) IEEE802.3an, (NBASE-T	IEEE802.3bz 2 x 10GBASE-T,	
Standards Compliance Number of Ports Data Transfer Rates	(10BASE-T) IEEE802.3, (100BASE-TX	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1	-Т)	-T) IEEE802.3an, (NBASE-T	IEEE802.3bz 2 x 10GBASE-T,	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols	(10BASE-T) IEEE802.3, (100BASE-TX	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1	-T) 10/100/1000 Mbps	-T) IEEE802.3an, (NBASE-T	IEEE802.3bz 2 x 10GBASE-T,	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services	(10BASE-T) IEEE802.3, (100BASE-TX	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT	T) 10/100/1000 Mbps P/IP	-T) IEEE802.3an, (NBASE-T	IEEE802.3bz 2 x 10GBASE-T,	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services Connector Type	(10BASE-T) IEEE802.3, (100BASE-TX	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT	-T) 10/100/1000 Mbps P/IP P, SFTP, NFS, SNMP	-T) IEEE802.3an, (NBASE-T	IEEE802.3bz 2 x 10GBASE-T,	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services Connector Type Other			1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT RJ Windows® 7, Windows Serve	-T) 10/100/1000 Mbps :P/IP P, SFTP, NFS, SNMP I-45		IEEE802.3bz 2 x 10GBASE-T, 2 x 1GBASE-T	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services Connector Type Ditert OS Support		dows® 10, Windows® 8.1, \	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT RJ Windows® 7, Windows Serve	-T) 10/100/1000 Mbps P/IP P, SFTP, NFS, SNMP J-45 r* 2016, Windows Server* Mac* OS* X 10.9 or later	2012 R2, Windows Server	IEEE802.3bz 2 x 10GBASE-T, 2 x 1GBASE-T	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services Connector Type Other Client OS Support	Win	dows® 10, Windows® 8.1, \ NAS Navigator	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT RJ Windows® 7, Windows Serve Windows Server® 2008, 2, NovaBACKUP® Buffalo Ed	T) 10/100/1000 Mbps P/IP P, SFTP, NFS, SNMP J-45 r* 2016, Windows Server* Mac* OS* X 10.9 or later lition (one server and ten w	⁰ 2012 R2, Windows Server vorkstation licenses)	IEEE802.3bz 2 x 10GBASE-T, 2 x 1GBASE-T	
Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services Connector Type Other Client OS Support Included Software Box Contents	Win	dows® 10, Windows® 8.1, \ NAS Navigator	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT RJ Windows® 7, Windows Serve Windows Server® 2008,	T) 10/100/1000 Mbps P/IP P, SFTP, NFS, SNMP J-45 r* 2016, Windows Server* Mac* OS* X 10.9 or later lition (one server and ten w	⁰ 2012 R2, Windows Server vorkstation licenses)	IEEE802.3bz 2 x 10GBASE-T, 2 x 1GBASE-T	
LAN Interface Standards Compliance Number of Ports Data Transfer Rates Supported Protocols Network File Services Connector Type Other Client OS Support Included Software Box Contents Accessories Compatible Hard Drives	Win	dows® 10, Windows® 8.1, \ NAS Navigator etup Guide, Cat 6a Etherne	1 (10GBASE-T), 2 (1GBASE- 2.5/5/10 Gbps / 1 TC CIFS/SMB, AFP, FT RJ Windows® 7, Windows Serve Windows Server® 2008, 2, NovaBACKUP® Buffalo Ed	10/100/1000 Mbps P/IP P, SFTP, NFS, SNMP J-45 P° 2016, Windows Server® Mac® OS® X 10.9 or later lition (one server and ten well held Key or Rail Kit with Mounted Server Rail Kit with Mounte	⁰ 2012 R2, Windows Server vorkstation licenses)	IEEE802.3bz 2 x 10GBASE-T, 2 x 1GBASE-T	





















^{* 3} year warranty on all products, including option of +1 / +2 year warranty extension. 5 years warranty only for TS51210RH, without warranty extension.