

RLK8-800B4-NVR-Kit-NVR-Specifications

	Model	RLN8-410
Video/Audio Input	IP Video Input	PoE IP Camera x 8
	Audio Input	Cameras with Built-in Mic
Video/Audio Output	HDMI Output	3840*2160, 1920*1080, 1440*900, 1280*1024, 1280*800, 1280*720, 1024*768
	VGA Output	1920*1080, 1440*900, 1280*1024, 1280*800, 1280*720, 1024*768
	Audio output	1CH RCA
Decoding	Live View/Playback Resolution	3840*2160, 2560x1920, 2560*1440, 2048*1536, 2304*1296, 1080p, 720p
	Frame Rate	PAL: 4CH@25fps; NTSC: 4CH@30fps
	Synchronous Playback	1CH@8MP; 4CH@4MP
HDD	SATA Devices	1 x 2TB SATA HDD
	Maximum Capacity	8TB (Maximum 4TB HDD/Port)
	External HDD	1 x eSATA
External Interface	USB Interface	2 x USB 2.0
	Network Interface	RJ45,10M/100M Ethernet, 8 Network Ports for IP camera, 1 Giga Network Port for LAN/WAN
PoE	Interface	8 Independent 100 Mbps PoE Network Interfaces
	Max. Power Consumption	25W
	Supported Standard	IEEE 802.3at
Network	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browser Supported	IE, Firefox, Chrome
	OS Supported	PC: Windows, Mac OS; SmartPhone: iOS, Android
	Max. User Access	20 Users
General	Power Supply	DC 48V/2A
	Power Consumption	<10W (Without HDD&PoE)
	Working Environment	Temperature: -10℃~+55℃ (14°F~131°F); Humidity: 10%~90%
	Dimensions (mm)	260(W) x 41(H) x 230(D)
	Weight (w/o HDD)	1.2 kg