







Put the seat on top of a table, this is the best working height.  
It is possible to mount this alone,  
But we recommend you being two persons for the assembly.  
Before you start the process, if necessary clean all holes from residue.



Fit the backrest on top of the seat, insert and screw loosely.  
Only use the tools provided for this!  
If you screw too tight you will have a hard time fitting the other side.



Fit the backrest on top of the seat, insert and screw loosely.  
Only use the tools provided for this!  
If you screw too tight you will have a hard time fitting the other side.



Time to get the plastic covers on.

For this you need a Philips or Frearson shaped screwdriver (NOT INCLUDED).

For the first cover you need 3 of the 5 small screws.

Start with the middle one and continue with the rest.





Get the cover that fits above, this one only requires 1 screw.  
Once mounted, get the last cover and attach it to the other side.  
When you are done it is time to start with the backplate.





Flip the chair and attach the backplate as shown in the picture above. Make sure the text and arrow that says "FRONT" are facing the right way. Attach two of the screws loosely, this can be done by hand. When it is fitted correctly, attach the last two screws and tighten.



Simply push the wheel down into the five star metal frame.  
Take the plastic cover for the gas lift and put it on.  
If there is a red plastic cap on top of the piston, remove it.





Insert the gaslift into the backplate like above.  
Then insert the five star metal base onto the gaslift as below!  
You have now finished the assembly for Torretta!



You have now finished the assembly for Torretta!

